

DRIVE TECHNOLOGY

INDIVIDUAL PRODUCT SOLUTION

Please contact us for your individual brake.



Made in Germany

Precision as passion
Certified management systems ISO 9001 and ISO 14001

PRECIMA Magnettechnik GmbH
Röcker Str. 16
D-31675 Bückeberg
Tel.: +49 (0) 5722-89332-0
Fax.: +49 (0) 5722-89332-2
E-Mail: info@precima.de
www.precima.de

2025 - v1.11




EN



FACTS



OPTIONS



- Redundant system
- Holding brake
- Fail-safe principle with emergency stop function
- Noise optimized
- Threaded holes for encoder attachment (tachobores)
- Protection class IP 54 when covered by a motor fan cover
- Reliable in continuous operation
- Ambient temperature -20°C up to +40°C

- Friction plate (Size 08 up to 26)
- Mounting flange
- Microswitch (function control)
- Inductive sensor (function control)
- Customized solutions on request



Size	Nominal braking torque MbN [Nm]	P [W] @ 20°C	b1	b2	$\phi d1 H7 / \phi d2 H7$	$\phi d6$	$\phi d7$	$\phi e1 (\pm 0,1)$	$\phi e2 (\pm 0,1)$	h	k1	k2	L	l	m	n	p	r	t	u	x	z
08	2x3,5/2x6	22	6	9,5	11/12/15*	26	85	72	34	1,5	3xM4	3xM4	82,6		18	1,5	8	44,3	110	55	46,3	89
10	2x7/2x12,5	28	7	10,5	11/12	32	105	90	40	1,5	3xM5	3xM5	102,4		20	2,5	10	54,5	120	65	54,5	111
13	2x14/2x25	34	9	12	15/20	42	130	112	54	1,5	3xM6	3xM6	115,2	800	20	3,5	12	62	160	75	62,5	132
15	2x28/2x50	45	9	12,5	20/25	52	150	132	65	1,5	3xM6	3xM6	129,6		25	3	12	69	200	85	68	151
17	2x42/2x75	55	11	14	25/30/35*	62	170	145	75	2	3xM8	3xM8	150,6		30	3	15	81	220	97	81	172
20	2x70/2x125	85	11	14	30/35/40	72	195	170	85	2	3xM8	3xM8	171,8		30	3	15	91	220	116	91	196
23	2x107/2x187	76	11	19	35/40/45	80	225	196	95	2	3xM8	3xM8	190,6		35	4,5	15	101	250	128	101	224
26	2x150/2x300	105	11	19	40/45/50	90	258	230	110	2	3xM10	3xM10	208,8	1000	40	4	25	110	330	148	109,6	258
30	2x250/2x500	140	19	17	50/55/60	115	306	278	138	12,5***	6xM10	6xM10	220		50	4	25	115,5	357	175	115,5	304
40**	2x800/2x1200	144	22	-	65/70/75/80*	150	400	360	180	18***	6xM12	6xM12	259,2		70	4	43	138,5	415	230	138,5	403

Errors and changes reserved

Dimensions in mm, standard keyway according to DIN 6885/1 - JS9

* Keyway according to DIN 6885/3 - JS9

** Only with fast acting rectifier (overexcitation)

*** No version with friction plate; screw-in groove or thickness for version with flange